



PPG1250B

Baudouin diesel generator | Open set

Designed and manufactured in the United Kingdom

1250 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Baudouin

12M33G1250/5

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Baudouin 12M33G1250/5

ALTERNATOR

Stamford S6L1D-G41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

1152 kVA

922 kW

STANDBY POWER / ESP

1269 kVA

1015 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
380	SS	1267	1014	1152	922
400	SS	1269	1015	1152	922

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

PPG1250B | Baudouin 12M33G1250/5 | Open set

ENGINE

Manufacturer	Baudouin
Model	12M33G1250/5
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	12
Arrangement	At Vee
Displacement	39.2L
Bore	150mm
Stroke	185mm
Compression ratio	15:1
Cooling	Liquid Cooled
Coolant capacity	188L
Oil capacity	160L

ALTERNATOR

Manufacturer	Stamford
Model	S6L1D-G41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	6
AVR	MX321
Voltage regulation	0.5%
Insulation class	H
Excitation	PMG
Winding	312
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 119.5 L/h	75% LOAD 175 L/h	100% LOAD 236.2 L/h	110% LOAD 262.6 L/h
-------------------------------------	-----------------------------------	--------------------------------------	--------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

Dimensions, weight, fuel tank and model-specific drawing are confirmed with the quotation.

No complete matching frame data is published for this selected configuration.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
12M33G1250/5	Stamford S6L1D-G41	400 / 3	1269	1152
12M33G1250/5	Leroy Somer LSA50.2M6	400 / 3	1272	1154

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12