



PPG1700B

Baudouin diesel generator | Open set

Designed and manufactured in the United Kingdom

1700 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Baudouin

12M33G1650/5

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Baudouin 12M33G1650/5

ALTERNATOR

Leroy Somer LSA50.2VL10

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

1562 kVA

1250 kW

STANDBY POWER / ESP

1678 kVA

1342 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
400	SS	1678	1342	1562	1250

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

PPG1700B | Baudouin 12M33G1650/5 | Open set

ENGINE

Manufacturer	Baudouin
Model	12M33G1650/5
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	12
Arrangement	At Vee
Displacement	39.2L
Bore	150mm
Stroke	185mm
Compression ratio	15:1
Cooling	Liquid Cooled
Coolant capacity	188L
Oil capacity	160L

ALTERNATOR

Manufacturer	Leroy Somer
Model	LSA50.2VL10
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	6
AVR	D350
Voltage regulation	0.5%
Insulation class	H
Excitation	Auxiliary Wound
Winding	6S
Harmonic content	<3.50%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 156.1 L/h	75% LOAD 234.2 L/h	100% LOAD 324 L/h	110% LOAD 354.2 L/h
-------------------------------------	-------------------------------------	------------------------------------	--------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

Dimensions, weight, fuel tank and model-specific drawing are confirmed with the quotation.

No complete matching frame data is published for this selected configuration.

SPECIFY YOUR PROJECT

Tell us your site load, required voltage and phase, prime or standby duty, ambient conditions and installation requirements. PPG will confirm a suitable build and its exact specification.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12