

PPG170BS

Baudouin diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

170 kVA

ROUNDED CATALOGUE CLASS



SELECTED CONFIGURATION

ENGINE

Baudouin 6M11G4D0/S

ALTERNATOR

Stamford UCI274F1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Representative PPG enclosure; final build may vary.

PRIME POWER / PRP

153 kVA

122 kW

STANDBY POWER / ESP

169 kVA

135 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	168	134	153	122
200	PS	169	135	153	122
208	PS	169	135	154	123
220	SD	168	134	153	122
230	SD	169	135	153	122
240	SD	169	135	154	123
380	SS	168	134	153	122
400	SS	169	135	153	122
415	SS	169	135	154	123

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

PPG170BS | Baudouin 6M11G4D0/S | Acoustic canopied

ENGINE

Manufacturer	Baudouin
Model	6M11G4D0/S
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	6.75L
Bore	105mm
Stroke	130mm
Compression ratio	18:1
Cooling	Liquid Cooled
Coolant capacity	20L
Oil capacity	19L

ALTERNATOR

Manufacturer	Stamford
Model	UCI274F1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 16.7 L/h	75% LOAD 24.6 L/h	100% LOAD 32.6 L/h	110% LOAD 36.1 L/h
------------------------------------	------------------------------------	-------------------------------------	-------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
3208 x 1164 x 1778	2287.5 kg	325 L

Reference frame 2400E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
6M11G4D0/S	KWise C274G120	400 / 3	165	150
6M11G4D0/S	Leroy Somer TAL044J	400 / 3	165	150
6M11G4D0/S	Mecc Alte ECP34-1L4C	380 / 3	165	150

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12