



PPG220CS

Cummins diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

220 kVA

ROUNDED CATALOGUE CLASS



SELECTED CONFIGURATION

ENGINE

Cummins QSB7G5

ALTERNATOR

Stamford UCI274H1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Representative PPG enclosure; final build may vary.

PRIME POWER / PRP

200 kVA

160 kW

STANDBY POWER / ESP

220 kVA

176 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	220	176	200	160
200	PS	220	176	200	160
208	PS	220	176	200	160
220	SD	220	176	200	160
230	SD	220	176	200	160
240	SD	220	176	200	160
380	SS	220	176	200	160
400	SS	220	176	200	160
415	SS	220	176	200	160

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.



Technical specification

PPG220CS | Cummins QSB7G5 | Acoustic canopied

ENGINE

Manufacturer	Cummins
Model	QSB7G5
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	6.69L
Bore	107mm
Stroke	124mm
Compression ratio	17.2:1
Cooling	Liquid Cooled
Coolant capacity	16.8L
Oil capacity	18.9L

ALTERNATOR

Manufacturer	Stamford
Model	UCI274H1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 26 L/h	75% LOAD 36 L/h	100% LOAD 45 L/h	110% LOAD 51 L/h
----------------------------------	----------------------------------	-----------------------------------	-----------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm) 3958 x 1504 x 2384	REFERENCE WEIGHT 2569.99 kg	FUEL TANK 500 L
--	--	----------------------------------

Reference frame 2900E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
QSB7G5	Leroy Somer TAL044M	400 / 3	220	200

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12