



PPG2300B

Baudouin diesel generator | Open set

Designed and manufactured in the United Kingdom

2300 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Baudouin

20M33G2250/5

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Baudouin 20M33G2250/5

ALTERNATOR

Stamford S7L1D-H41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

2107 kVA

1686 kW

STANDBY POWER / ESP

2309 kVA

1847 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
380	SS	2290	1832	2107	1686
400	SS	2309	1847	2107	1686

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.



Technical specification

PPG2300B | Baudouin 20M33G2250/5 | Open set

ENGINE

Manufacturer	Baudouin
Model	20M33G2250/5
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	20
Arrangement	At Vee
Displacement	65.4L
Bore	150mm
Stroke	185mm
Compression ratio	15:1
Cooling	Liquid Cooled
Coolant capacity	397L
Oil capacity	235L

ALTERNATOR

Manufacturer	Stamford
Model	S7L1D-H41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	6
AVR	MX341
Voltage regulation	1%
Insulation class	H
Excitation	PMG
Winding	312
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 223.4 L/h	75% LOAD 326.9 L/h	100% LOAD 432.8 L/h	110% LOAD 478 L/h
-------------------------------------	-------------------------------------	--------------------------------------	------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

Dimensions, weight, fuel tank and model-specific drawing are confirmed with the quotation.

No complete matching frame data is published for this selected configuration.

SPECIFY YOUR PROJECT

Tell us your site load, required voltage and phase, prime or standby duty, ambient conditions and installation requirements. PPG will confirm a suitable build and its exact specification.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12