

PPG280BS

Baudouin diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

280 kVA

ROUNDED CATALOGUE CLASS



SELECTED CONFIGURATION

ENGINE

Baudouin 6M16G6D0/S

ALTERNATOR

Stamford UCDI274K1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Representative PPG enclosure; final build may vary.

PRIME POWER / PRP

250 kVA

200 kW

STANDBY POWER / ESP

275 kVA

220 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	275	220	250	200
200	PS	275	220	250	200
208	PS	275	220	250	200
220	SD	275	220	250	200
230	SD	275	220	250	200
240	SD	275	220	250	200
380	SS	275	220	250	200
400	SS	275	220	250	200
415	SS	275	220	250	200

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

PPG280BS | Baudouin 6M16G6D0/S | Acoustic canopied

ENGINE

Manufacturer	Baudouin
Model	6M16G6D0/S
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	9.726L
Bore	126mm
Stroke	130mm
Compression ratio	17:1
Cooling	Liquid Cooled
Coolant capacity	42L
Oil capacity	30L

ALTERNATOR

Manufacturer	Stamford
Model	UCDI274K1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 28.3 L/h	75% LOAD 42.2 L/h	100% LOAD 56.9 L/h	110% LOAD 63.4 L/h
------------------------------------	------------------------------------	-------------------------------------	-------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
3958 x 1504 x 2384	3114.75 kg	500 L

Reference frame 2900E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
6M16G6D0/S	KWise C274G200	400 / 3	275	250
6M16G6D0/S	Leroy Somer TAL046D	400 / 3	275	250

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12