

PPG30BS

Baudouin diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

30 kVA

ROUNDED CATALOGUE CLASS



Representative PPG enclosure; final build may vary.

SELECTED CONFIGURATION

ENGINE

Baudouin 4M06G4D0/S

ALTERNATOR

Stamford S1L2-J1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

PRIME POWER / PRP

23.7 kVA

19 kW

STANDBY POWER / ESP

25.7 kVA

20.6 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
200	PS	25.7	20.6	23.7	19
208	PS	25.7	20.6	23.8	19
230	SD	25.7	20.6	23.7	19
240	SD	25.7	20.6	23.8	19
400	SS	25.7	20.6	23.7	19
415	SS	25.7	20.6	23.8	19

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.

Technical specification

PPG30BS | Baudouin 4M06G4D0/S | Acoustic canopied

ENGINE

Manufacturer	Baudouin
Model	4M06G4D0/S
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	4
Arrangement	In Line
Displacement	2.3L
Bore	89mm
Stroke	92mm
Compression ratio	17.5:1
Cooling	Liquid Cooled
Coolant capacity	8.6L
Oil capacity	11.5L

ALTERNATOR

Manufacturer	Stamford
Model	S1L2-J1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS540
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>100%

REFERENCE FUEL CONSUMPTION

50% LOAD 3.2 L/h	75% LOAD 4.5 L/h	100% LOAD 6.1 L/h	110% LOAD 7.1 L/h
-----------------------------------	-----------------------------------	------------------------------------	------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm) 2240 x 1038 x 1378	REFERENCE WEIGHT 969 kg	FUEL TANK 80 L
--	--	---------------------------------

Reference frame 1900E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
4M06G4D0/S	Leroy Somer TAL042A	400 / 3	25.5	23.5
4M06G6D0/S	Stamford S1L2-Y1	230 / 1	32.8	29.9

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12