



PPG450P

Perkins diesel generator | Open set

Designed and manufactured in the United Kingdom

450 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Perkins

2206A-E13TAG3

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Perkins 2206A-E13TAG3

ALTERNATOR

Leroy Somer TAL0473A

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

406 kVA

325 kW

STANDBY POWER / ESP

450 kVA

360 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
400	SS	450	360	406	325

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.



Technical specification

PPG450P | Perkins 2206A-E13TAG3 | Open set

ENGINE

Manufacturer	Perkins
Model	2206A-E13TAG3
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Electronic
Cylinders	6
Arrangement	In Line
Displacement	12.5L
Bore	130mm
Stroke	157mm
Compression ratio	16.3:1
Cooling	Liquid Cooled
Coolant capacity	51.4L
Oil capacity	40.0L

ALTERNATOR

Manufacturer	Leroy Somer
Model	TAL0473A
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	6
AVR	R150
Voltage regulation	1.0% Regulation%
Insulation class	H
Excitation	Brushless
Winding	6S
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 42 L/h	75% LOAD 62 L/h	100% LOAD 81 L/h	110% LOAD 90 L/h
---------------------------	---------------------------	----------------------------	----------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
3015 x 1180 x 2057	3019.1 kg	730 L

Reference frame 9007GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
2506A-E15TAG1	Leroy Somer TAL0473A	400 / 3	450	410

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12