

PPG570SS

Scania diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

570 kVA

ROUNDED CATALOGUE CLASS



SELECTED CONFIGURATION

ENGINE

Scania DC16093A-02-51

ALTERNATOR

Stamford HCI544E1

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Representative PPG enclosure; final build may vary.

PRIME POWER / PRP

520 kVA

416 kW

STANDBY POWER / ESP

571 kVA

457 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
190	PS	569	455	519	415
200	PS	571	457	520	416
208	PS	572	458	520	416
220	PS	573	458	521	417
220	SD	569	455	518	414
230	SD	571	457	520	416
240	SD	572	458	520	416
254	SD	573	458	521	417
380	SS	569	455	518	414
400	SS	571	457	520	416
415	SS	572	458	520	416
440	SS	573	458	521	417

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.



Technical specification

PPG570SS | Scania DC16093A-02-51 | Acoustic canopied

ENGINE

Manufacturer	Scania
Model	DC16093A-02-51
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	8
Arrangement	At Vee
Displacement	16.4L
Bore	130mm
Stroke	154mm
Compression ratio	16.7:1
Cooling	Liquid Cooled
Coolant capacity	68L
Oil capacity	48L

ALTERNATOR

Manufacturer	Stamford
Model	HCI544E1
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	12
AVR	AS440
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	311
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 52.3 L/h	75% LOAD 75.6 L/h	100% LOAD 100.3 L/h	110% LOAD 111.5 L/h
------------------------------------	------------------------------------	--------------------------------------	--------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm) 4908 x 2164 x 2658	REFERENCE WEIGHT 5666.8 kg	FUEL TANK 1120 L
--	---	-----------------------------------

Reference frame 5100E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
DC16093A-02-51	Stamford S5L1D-D41	400 / 3	568	516

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12