



PPG70P

Perkins diesel generator | Open set

Designed and manufactured in the United Kingdom

70 kVA

ROUNDED CATALOGUE CLASS

ENGINE PLATFORM

Perkins

1103A-33TG2

Model-specific drawing supplied with quotation.

SELECTED CONFIGURATION

ENGINE

Perkins 1103A-33TG2

ALTERNATOR

Leroy Somer TAL042H

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Configuration and appearance are confirmed with the quotation.

PRIME POWER / PRP

60 kVA

48 kW

STANDBY POWER / ESP

66 kVA

53 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
400	SS	66	53	60	48

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.



Technical specification

PPG70P | Perkins 1103A-33TG2 | Open set

ENGINE

Manufacturer	Perkins
Model	1103A-33TG2
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	Mechanical
Cylinders	3
Arrangement	In Line
Displacement	3.3L
Bore	105mm
Stroke	127mm
Compression ratio	17.25:1
Cooling	Liquid Cooled
Coolant capacity	10.2L
Oil capacity	8.3L

ALTERNATOR

Manufacturer	Leroy Somer
Model	TAL042H
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	6
AVR	R120
Voltage regulation	1%
Insulation class	H
Excitation	Self Excited
Winding	6S
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 7.56 L/h	75% LOAD 10.8 L/h	100% LOAD 14.6 L/h	110% LOAD 15.9 L/h
------------------------------------	------------------------------------	-------------------------------------	-------------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm) 1700 x 702 x 1388	REFERENCE WEIGHT 811.9 kg	FUEL TANK 125 L
---	--	----------------------------------

Reference frame 9045GA (Export). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
1104A-44TG1	Stamford UCI224F1	400 / 3	72	66
1104A-44TG1	Stamford UCI224G1	400 / 3	72	66
1103A-33TG2	Stamford S1L2-Y1	400 / 3	66	61
1104A-44TG1	Leroy Somer TAL044A	400 / 3	72	66

Engineering data above apply only to the selected configuration on page 1. 2 further class configurations are listed on the product page.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12