

PPG830BS

Baudouin diesel generator | Acoustic canopied

Designed and manufactured in the United Kingdom

830 kVA

ROUNDED CATALOGUE CLASS



SELECTED CONFIGURATION

ENGINE

Baudouin 6M33G825/5

ALTERNATOR

Stamford S6L1D-C41

ELECTRICAL OUTPUT

400 V | 3-phase | 50 Hz

Representative PPG enclosure; final build may vary.

PRIME POWER / PRP

772 kVA

618 kW

STANDBY POWER / ESP

829 kVA

663 kW

Ratings shown at 400 V, 3-phase, 50 Hz. The PPG model number is a rounded class; use the exact ratings for selection.

PUBLISHED ELECTRICAL RATINGS

Voltage (V)	Connection	ESP (kVA)	ESP (kW)	PRP (kVA)	PRP (kW)
380	SS	829	663	771	617
400	SS	829	663	772	618

PRP = prime power. ESP = emergency standby power. Values apply to the selected engine and alternator above. Connection codes follow the reference specification and must be confirmed before installation.



Technical specification

PPG830BS | Baudouin 6M33G825/5 | Acoustic canopied

ENGINE

Manufacturer	Baudouin
Model	6M33G825/5
Aspiration	Turbocharged
Combustion	Direct Injection
Cycle	4 Stroke
Governor	ECU
Cylinders	6
Arrangement	In Line
Displacement	19.6L
Bore	150mm
Stroke	185mm
Compression ratio	15:1
Cooling	Liquid Cooled
Coolant capacity	94L
Oil capacity	64L

ALTERNATOR

Manufacturer	Stamford
Model	S6L1D-C41
Type	Brushless
Phases	3
Bearings	1
Poles	4
Leads	6
AVR	MX321
Voltage regulation	0.5%
Insulation class	H
Excitation	PMG
Winding	312
Harmonic content	<5.00%
Short circuit	>300%

REFERENCE FUEL CONSUMPTION

50% LOAD 77.4 L/h	75% LOAD 114.8 L/h	100% LOAD 159.5 L/h	110% LOAD 174.8 L/h
-----------------------------	------------------------------	-------------------------------	-------------------------------

Reference figures vary with operating conditions and the confirmed duty.

INSTALLATION INFORMATION

L x W x H (mm)	REFERENCE WEIGHT	FUEL TANK
4908 x 2164 x 2658	7143.25 kg	1120 L

Reference frame 5100E (UK/EU). Drawing, weights and tank capacity are subject to the ordered build.

OTHER CONFIGURATIONS IN THIS CATALOGUE CLASS

Engine	Alternator	V / phase	ESP kVA	PRP kVA
6M33G825/5	Stamford S5L1D-H41	400 / 3	825	750
6M33G6D0/S	Stamford S5L1D-H41	400 / 3	824	750
6M33G6D0/S	Leroy Somer TAL049C	400 / 3	827	769

Engineering data above apply only to the selected configuration on page 1.

Final enclosure, controls, protection, acoustics and emissions suitability must be specified for the project. This sheet is a configuration guide, not an installation drawing.

PPG technical specification | Reviewed 2026-10-12